

PROTORQUE

BREAK-OUT FRAME

Used primarily for CRT tools, the vise and adjustable roller stand allows you to both make and break connections. This is accomplished inside of the same footprint by simply shifting or rotating the tool. The Break-Out Frame's compact footprint and mobile support stand allow the assembly to be installed into the smallest areas. A variety of torque ratings are available upon request. From make-up to break-out in mere minutes.

REDEFINE TRS™

- SLIDING HEAD AND ROLLER DESIGN ALLOWS FOR A QUICK CHANGE OVER FROM MAKE-UP TO BREAK-OUT
- COMPACT DESIGN FOR TRANSPORT AND REDUCES SHOP SPACE



CANADA
780.933.0404

UNITED STATES
713.300.5216

PROTORQUETECH.COM



PROTORQUE BREAK-OUT FRAME



SPECIFICATIONS

- **TORQUE RATING:** 40,000 – 90,000 ft/lbs (54,230 – 12,2025 Nm)
- **TUBULAR OD RANGE:** 4 – 14" OD
- **DIMENSIONS:** Length 60" (1,524 mm), Width 46" (1,168 mm), Height 56" (1,422 mm)
- **WEIGHT:** 1,500 lbs (680 kg)
- **PRESSURE RATING:** 3,000 PSI (20,700 kPa)
- **HYDRAULIC FLOW REQUIREMENTS:** 2 – 8 gal/min (7.5 – 30.5 L/min)

FEATURES:

Sliding head design allow for vise or adjustable roller to be moved for make / break operations

Lift ram for installation and removal of tong after operation

Independent hydraulic control stand available upon request

Low flow hydraulic system allows for controlled use

CANADA
780.933.0404

UNITED STATES
713.300.5216

PROTORQUETECH.COM

